

KAPPAFLEX 2 CO SMOOTH

1104-17



Product group	100
Inner tube	Synthetic oil resistant rubber
Cover	Weather and oil resistant rubber
Temperature min. °C	-40
Temperature max. °C	+100
Media	Oil
Reinforcement	Two layers of steel wire
Safety factor	1:4
Applications and characteristics	Ozone resistant hose for applications with high pressures, well suited for marine applications. Exceeds EN 857 2SC. Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters per length.
Design	Smooth green and orange branding
Ferrule	4200-11-xx, 4200-23-xx, 4200-31-xx

Media



Part no.	ID mm	ID inch	OD mm	Bend rad mm	Weight kg/m	Max length	WP MPa	Length min.
11041704	6.50	1/4"	13,4	75	0,30	-	42.50	-
11041705	8	5/16"	15	85	0,35	-	40	-
11041706	10	3/8"	17,2	90	0,42	-	35	-
11041708	13	1/2"	20,4	130	0,52	-	31	-
11041710	16	5/8"	23,9	160	0,66	-	28	-
11041712	19	3/4"	27,7	195	0,86	-	28	-
11041716	25	1"	35,4	250	1,17	-	21	-
1104170430	6.50	1/4"	13,4	75	0,30	260	42.50	-
1104170630	10	3/8"	17,2	90	0,42	175	35	-
1104170830	13	1/2"	20,4	130	0,52	125	31	-
1104171230	19	3/4"	27,7	195	0,86	145	28	-