

TRANSPARENT SILICON HOSE

1529



Product group	140
Inner tube	Silicon
Cover	Silicon
Temperature min. °C	-50
Temperature max. °C	+200
Media	Air pressure, food and beverage, special, water
Reinforcement	None
Applications and characteristics	Unreinforced silicon hose suitable for air pressure, water, food and beverage and alcohol up to 50 %. The hose resists repeated sterilisation cycles with a maximum temperatur of 240°C, for short periods.

Media



Part no.	ID mm	OD mm	Weight kg/m	Length m/coil
15290115	1	1,5	0,0013	25
15290102	1	2	0,003	25
15290103	1	3	0,008	25
15290203	2	3	0,005	25
15290205	2	5	0,021	25
15290304	3	4	0,009	25
15290305	3	5	0,016	25
15290306	3	5	0,027	25
15290406	4	6	0,0205	25
15290407	4	7	0,029	25
15290408	4	8	0,049	25
15290508	5	8	0,0385	25
15290509	5	9	0,057	25
15290510	5	10	0,076	25
15290608	6	8	0,0285	25
15290609	6	9	0,046	25
15290610	6	10	0,065	25
15290612	6	12	0,106	25
15290710	7	10	0,042	25
15290711	7	11	0,046	25
15290810	8	10	0,0365	25
15290811	8	11	0,0575	25
15290812	8	12	0,081	25

Part no.	ID mm	OD mm	Weight kg/m	Length m/coil
15290813	8	13	0,106	25
15290814	8	14	0,117	25
15290912	9	12	0,0635	25
15291014	10	14	0,097	25
15291016	10	16	0,1575	25
15291012	10	12	0,0445	25
15291015	10	15	0,1265	25
15291018	10	18	0,19	25
15291216	12	16	0,113	25
15291318	13	18	0,157	25
15291520	15	20	0,175	25
15291521	15	21	0,20	25
15291523	15	23	0,24	25
15291525	1.50	2,5	0,004	25
15291619	16	19	0,115	25
15291622	16	22	0,239	25
15291625	16	25	0,296	25
15291824	18	24	0,252	25
15291922	19	22	0,136	25
15292025	20	25	0,22	25
15292027	20	27	0,24	25
15292505	2.50	5	0,019	25
15292532	25	32	0,30	25